

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International publication date

14 April 2005 (14.04.2005)

PCT

(10) International publication number

WO 2005/033608 A1

(51) International patent classification⁷: F28F 9/00

(21) International application number: PCT/EP2004/010265

(22) International filing date: 14 September 2004 (14.09.2004)

(25) Language of filing: German

(26) Language of publication: German

(30) Data relating to the priority:
103 44 219.7 22 September 2003 (22.09.2003) DE

(71) Applicant (for all designated States except US): BEHR GMBH & CO. KG [DE/DE]; Mauserstrasse 3, 70469 Stuttgart (DE).

(72) Inventors; and

(75) Inventors/Applicants (US only): HASSDENTEUFEL, Klaus [DE/DE]; Richthofenstrasse 15, 70839 Gerlingen (DE). KURZ, Volker [DE/DE]; Stedinger Strasse 40, 70499

Stuttgart (DE). NGUYEN, Chi-Duc [VN/DE]; Böblinger Strasse 46, 70199 Stuttgart (DE). SCHWEIDLER, Dieter [DE/DE]; Wilhelmstrasse 21/1, 71739 Oberriexingen (DE). SPIETH, Michael [DE/DE]; Albstrasse 33, 72810 Gomaringen (DE).

(74) Joint Representative: BEHR GMBH & CO. KG; Intellectual Property, G-IP, Mauserstrasse 3, 70469 Stuttgart (DE).


(81) Designated states (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[continued on next page]

As printed

(54) Title: HEAT EXCHANGER MODULE FOR A MOTOR VEHICLE

(54) Bezeichnung: WÄRMEÜBERTRAGERMODUL FÜR EIN KRAFTFAHRZEUG



WO 2005/033608 A1

(57) Abstract: The invention relates to a heat exchanger module (1) for a motor vehicle, comprising at least one heat exchanger (2), preferably a coolant cooler, and laterally arranged plastic module supports (11, 12) which retain the heat exchanger module (1) and support the same on the vehicle. According to the invention, the heat exchanger (2) is provided with two receptacles (4, 5) having two longitudinal faces, one lateral face, and two front faces (4a, 4b, 4c; 5a, 5b, 5c) while the module supports are embodied as slip-on boxes (11, 12) which have the shape of the receptacles (4, 5), embrace the longitudinal, lateral, and front faces (4a, 4b, 4c-, 5a, 5b, 5c) thereof in a positive manner, and are secured to the front faces (4c, 5c) by means of locking hooks and/or snap-in hooks.

[continued on next page]

(84) **Designated states** (unless otherwise indicated, for every kind of regional protection available): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- With International Search Report.
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For an explanation of the two-letter codes and the other abbreviations, reference is made to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular edition of the PCT Gazette.

Declaration under Rule 4.17

-- of inventorship (Rule 4.17(iv)) for the following designation US

(57) **Zusammenfassung:** Die Erfindung betrifft ein Wärmeübertragermodul (1) für ein Kraftfahrzeug, bestehend aus mindestens einem Wärmeübertrager (2), vorzugsweise einem Kühlmittelkühler sowie aus seitlich angeordneten, das Wärmeübertragermodul (1) haltenden und am Fahrzeug abstützenden Modulträgern (11, 12) aus Kunststoff. Es wird vorgeschlagen, dass der Wärmeübertrager (2) zwei Sammelkästen (4, 5) mit zwei Längs-, einer Seiten- sowie zwei Stirnflächen (4a, 4b, 4c; 5a, 5b, 5c) aufweist und dass die Modulträger als Stülpkästen (11, 12) in der Form der Sammelkästen (4, 5) ausgebildet sind, deren Längs-, Seiten- und Stirnflächen (4a, 4b, 4c-, 5a, 5b, 5c) formschlüssig umgreifen und an den Stirnflächen (4c, 5c) durch Rasthaken und/oder Schnapphaken gesichert sind.